# Product datasheet Characteristics

## NSYPLM43G

wall-mounting enclosure polyester monobloc IP66 H430xW330xD200mm



Price\*: 88.20 GBP



#### Main

- Indiri		
Range	Thalassa	
Product name	Thalassa PLM	
Device short name	PLM	
Enclosure type	Multi-purpose	
Category	Compact enclosure	
Nominal height	430 mm	
Nominal width	330 mm	
Nominal depth	200 mm	
Enclosure mounting	Wall mounted	
Device composition	1 body 1 door 2 lock	
Body type	One piece moulded with notches in the rear Built-in canopy	
Door type	Plain	
Lock type	3 mm double-bar lock	

#### Complementary

Number of locks	2	
Mounting plate description	Without mounting plate	-
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Polyester reinforced with fibreglass	
Colour	Grey (RAL 7035)	
Standards	NEMA classification 4X NEMA classification 13 IEC 62208	ŗ
Product certifications	UL	

#### Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-3590 °C

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

#### Contractual warranty

Warranty	18 months