

Power Supply Cabinet EX

ATEX-approved 316 stainless steel power supply cabinet with corrosion-resistant epoxy paint finish. Pre-mounted with fuses, terminals, RJ45 coupler and 115/230 V AC transformer providing 24 V AC for XF40 and XP40 Explosion Protected Network Cameras, as well as Washer Tank EX. The cabinet has three open M20 cable entries and a fourth plugged entry and is EX II 2GD, EX d IIB Gb, EX tb IIIC Db IP66 certified for temperatures between -40°C and +55°C.



Power Supply Cabinet EX

Power Supply Cabinet EX

General	
Supported cameras	AXIS XF40 Series AXIS XP40 Series
Casing	IP66-rated SAE 316 stainless steel casing Corrosion-resistant epoxy paint finish Cable entries: 4x M20x1.5P 1x Entry fitted with certified stainless steel plug and fibre washer For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Sustainability	PVC free
Environment	Indoor/Outdoor
Power	Input: 120 V AC, max. 1.5 A 230 V AC, max. 0.75 A 24 V AC, max. 5 A
	Output: 24 V AC, 120W, max. 5 A PVC free
Operating conditions	-40°C to 55 °C (-40°F to 12.7 °F) Humidity 10–100% RH (condensing)
Approvals	ATEX approved: Exd IIB Gb, Ex tb IIIC Db, IP66 EN50014, EN50018/EN60079-0, EN60079-1, EN60079-31
Connectors	RJ45 Coupler, CAT6, Shielded
Weight	85 Kg (187 lb)
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Environmental responsibility: www.axis.com/environmental-responsibility	